



User guide YAX12A

www.xpaudiopro.com

12" Powered loudspeaker with bluetooth audio Pa System



IMPORTANT INSTRUCTION

For your own safety please read this user manual carefully before installing the device.

SAFETY INTRODUCTION

- *If this speaker has been exposed to significant temperature changes due to storage or transportation changes, do not switch it on immediately. Leave the speaker switched off until it has reached room temperature.
- *It is essential that the device is earthed. A qualified person must carry out the electric connection.
- *Make sure that the available voltage is not higher than stated at the end of this manual.
- *Make sure the power cord is never crimped or damaged before and during use.
- *Only handle the power cord by plug. Never pull out the plug by tugging the power cord.
- *Turn off power before disconnecting electric.

CAUTION:

- 1. Please be aware that damages caused by user modification, misuse, physical abuse or any unusual activities will void the warranty.
- 2. Use this speaker at safe listening volumes.

GENERAL GUIDELINES

- *Operate this speaker only after reading this user manual.
- *Please use the original packaging if the device is to be transported.
- *For safety reasons, do not remove any speaker components or rear panel.



12" Powered loudspeaker with bluetooth audio Pa System



The XP Audio YAX12A is a powerful active sound system designed to deliver clarity, versatility, and reliable performance for all types of events. Equipped with a 12" woofer and a titanium compression driver, it provides clear and dynamic sound across the entire frequency range. Its Class-D amplifier offers 450 W RMS output, ensuring punchy bass and crisp highs, while Bluetooth connectivity adds flexibility for wireless streaming. Built with a durable enclosure and designed for easy transport, it delivers both power and mobility without compromise.



TECHNICAL SPECIFICATIONS

| Model Name | YAX12A |
|--------------------|------------------------------------|
| Power | 450w RMS/1800w PEAK |
| Amplifier | Class H (DSP-103 4modes) |
| Woofer | 12" (SCW127537-4) 60oz 3.0" VC |
| Driver | 1.75" Titanium (CD-44) 1.75" VC |
| Nominal Impedance | 4 Ohm |
| Frequency Response | 45Hz - 20KHz |
| Sensitivity | 123dB Max SPL |
| Line input | 6.35 & XLR Jack combo |
| Mic Input | 6.35 & XLR Jack combo |
| Output | 1 ch XLR Line Output |
| Media Player | Bluetooth |
| TWS | Yes |
| Cabinet Material | PP Hard Plastic |
| Weight | 22,40 kg |
| Dimensions (W×H×D) | 41.5×66×40cm |

12" Powered loudspeaker with bluetooth audio Pa System




OPERATION GUIDE

- 1. DSP Set(USB Interface to Computer)
- 2. LCD Screen:

DSP Main Menu: MODE / EQ/ SET UP/EXIT

- 3. Push for DSP Control
- 4. BLUETOOTH Switch ON/OFF
- 5. MIX OUT: XLR
- 6. LINE/MIC Input Volumn Control A/B
- 7. LINE / MIC Input Switch
- 8. 2ch XLR & 1/4" Combo Input
- 9. Power Switch on/off
- 10. AC Input





Bluetooth Pairing

Once the MODE button is selected to BT, the Bluetooth pairing signal is sent waiting for a device to pair.

Only one subwoofer can pair with one Bluetooth device.

To connect two Subwoofers with Bluetooth, pair the first subwoofer to your device and connect and XLR connecting cable to the second subwoofer.



Sound efficiency redefined

Manufactured and distributed by:

La Polla S.A. Cuit: 30-71140161-6 Argentina www.xpaudiopro.com